


2S110Q-047F0



- Phase Current (A): 6.5
- Holding Torque (Nm): 21

Rating: Not Rated Yet

Price

Sales price without tax 300,00 €

[Ask a question about this product](#)

Manufacturer [Maker: Kinco](#)

Description	Technical Specifications	2S110Q-047F0
	Step Angle	1.8°
	Phase Current (A)	6.5
	Holding Torque (Nm)	21
	Damping Torque (Nm)	0.59
	Winding Resistance (?)	0.72±10%
	Winding Inductance (mH)	12.8±20%
	Motor Inertia (kg.cm)	10.9
	Motor Length L (mm)	150
	Shaft Diameter (mm)	19
	Number Of Lead Wires	4
	Insulation Class	B
	Withstand	1200VAC 1S

Stepper Motors: 2S110Q-047F0

Voltage Level	5mA
Max. Axial Load (N)	60
Max. Radial Load (N)	220
Operating Temperature	-20??+50?
Surface Temperature Rise	Max.80? (Both Phases Connected With Rated Current)
Insulation Impedance	Minimum 100M?, 500V DC
Weight (kg)	8.4
Startup With Load(Hz)*	4.5K
Ingress Protection	IP40

[2S110Q-047F0 Dimensions](#)

[KincoCatalog Stepper](#)