CM880B





- 3 Opto-Isolation Digital Signal Input Channels, 3 Channels Support Voltage Range 5~24VDC
- Support CW/CCW, PLS+DIR
- Non-Isolation RS485 Interfaces, Support Modbus Protocol
- Multiple I/O Functions, Support Homing, Multi-Speed, Multi-position, etc
- Support Automatic Parameter Adjustable Regulation, Self-Defined Shalf-Lock, Step Smooth Filter
- Over-Voltage, Under-Voltage, Overheat And Over-Current Protection
- Support RS232 Communication, Parameter Settings By KincoStep Software

Rating: Not Rated Yet
Price
Sales price without tax 150,00 €

Ask a question about this product

ManufacturerMaker: Kinco

Description

Technical Specifications	
Input Voltage	24 ~ 70VDC
Over Voltage Protection	85VDC
Under Voltage Protection	15VDC
Output Current	0.15 ~ 8A (Peak)
Subdivision	Set By KincoStep Software
Adaptable Motor	2&3 Phase Hybrid Stepper Motor
Control Mode	I/O Control; Modbus Control; Pulse Control: PLS+DIR, CW/CCW
Cooling Method	Natural Air Cooling

Operation Environment	Avoid The Environment With A Great Amount Of Metallic Powder, Oil Mist, Or Erosive Gases.
Operation Humidity	<85%, RH (Non-Condensing Or Water Drops)
Operation Temperature	0? ~ 40?
Storage Temperature	-20? ~ 70?
Weight (Net)	0.25kg
Dimensions	118 X 75.5 X 34mm
Ingress Protection	IP20

CM880B Dimensions

KincoCatalog Stepper