

## CM880C



- 3 Opto-Isolation Digital Signal Input Channels, 3 Channels Support Voltage Range 5-24VDC
- Support CW/CCW, PLS+DIR;
- Non-Isolation CAN Interfaces, Support CANopen Protocol
- Multiple I/O Functions, Support Homing, Multi-Speed, Multi-Position, etc
- Support Automatic Parameter Adjustable Regulation, Self-Defined Shalf-Lock, Step Smooth Filter
- Over-Voltage, Under-Voltage, Overheat And Over-Current Protection
- Support RS232 Communication, Parameter Settings By KincoStep Software

Rating: Not Rated Yet

**Price**

Sales price without tax 175,00 €

[Ask a question about this product](#)

Manufacturer [Maker: Kinco](#)

Description	Technical Specifications	
	<b>Input Voltage</b>	24 ~ 70VDC
<b>Over-Voltage Protection</b>	85VDC	
<b>Under-Voltage Protection</b>	15VDC	
<b>Phase Current (Peak)</b>	0.15 ~ 8A (Peak)	
<b>Subdivision</b>	Set By KincoStep Software	
<b>Adaptable Motor</b>	2&3 Phase Hybrid Stepper Motor	
<b>Control Mode</b>	I/O Control CANopen Control	

	Pulse Control: PLS+DIR, CW/CCW
<b>Cooling Method</b>	Natural Air Cooling
<b>Operation Environment</b>	Avoid The Environment With A Great Amount Of Metallic Powder, Oil Mist, Or Erosive Gases.
<b>Operation Humidity</b>	<85%, RH (Non-Condensing Or Water Drops)
<b>Operation Temperature</b>	0? ~ 40?
<b>Storage Temperature</b>	-20? ~ 70?
<b>Weight</b>	0.25kg
<b>Dimensions</b>	118 X 75.5 X 34mm
<b>Ingress Protection</b>	IP20

[CM880C Dimensions](#)

[KincoCatalog\\_Stepper](#)