

DRC-60B



- Universal AC input / Full range
- Protections: Short circuit / Overload / Over voltage
- Battery low protection / Battery reverse polarity protection by fuse
- Can be installed on DIN rail TS-35/7.5 or 15
- Alarm signal for AC OK and Battery low via relay contact
- Cooling by free air convection
- Pass LPS
- LED indicator for power on
- 100% full load burn-in test
- 3 years warranty

Rating: Not Rated Yet

Price

Sales price without tax 47,50 €

[Ask a question about this product](#)

Manufacturer [Maker: Mean Well](#)

Description

SPECIFICATION			
MODEL		DRC-60B	
OUTPUT NUMBER	DC VOLTAGE	27.6V	27.6V
	RATED CURRENT	1.4A	0.75A
	CURRENT RANGE	0 ~ 2.15A	-----
	RATED POWER	59.34W	
	RIPPLE & NOISE (200mV p-p	-----
	Note.2		

	VOLTA GE ADJ. RANGE	CH1:24 ~ 30V
	VOLTA GE TO LERAN CE Note.3	±1.0% -----
	LINE R EGULA TION	±0.5% -----
	LOAD REGUL ATION	±0.5% -----
	SETUP, RISE TIME Note.4	400ms, 50ms/230VAC 800ms, 50ms/115VAC at full load
	HOLD UP TIME (Typ.)	50ms/230VAC 10ms/115VAC at full load
INPUT	VOLTA GE RANGE	90 ~ 264VAC 127 ~ 370VDC [DC input operation possible by connecting AC/L(+), AC/N(-)]
	FREQU ENCY RANGE	47 ~ 63Hz
	EFFICI ENCY (Typ.)	88%
	AC CU RRENT (Typ.)	1.3A/115VAC 0.8A/230VAC
	INRUS H CUR RENT (Typ.)	COLD START 30A/115VAC 60A/230VAC
	PROTE CTION	OVERL OAD
OVER VOLTA GE		CH1:28.98 ~ 37.26V Protection type : Shut down o/p voltage, re-power on to recover
BATTE RY CUT OFF		20±1V
FUNCT ION	AC OK	Relay contact output, ON : AC OK ; OFF : AC Fail ; max. rating :

		30V/1A
	BATTERY LOW	Relay contact output, OFF : Battery OK ; ON : Battery Low ; max. rating : 30V/1A
		Battery low voltage : < 22V
ENVIRONMENT	WORKING TEMP.	-30 ~ +70°C (Refer to "Derating Curve")
	WORKING HUMIDITY	20 ~ 90% RH non-condensing
	STORAGE TEMP., HUMIDITY	-40 ~ +85°C , 10 ~ 95% RH
	TEMP. COEFFICIENT	±0.03%/°C (0 ~ 50°C) on CH1 output
	VIBRATION	10 ~ 500Hz, 2G 10min./1cycle, 60min. each along X, Y, Z axes
SAFETY & EMC (Note 5)	SAFETY STANDARDS	UL60950-1, TUV EN60950-1, EAC TP TC 004 approved
	WITHSTANDING VOLTAGE	I/P-O/P:3KVAC I/P-FG:2KVAC O/P-FG:0.5KVAC
	ISOLATION RESISTANCE	I/P-O/P, I/P-FG, O/P-FG:100M Ohms / 500VDC / 25°C / 70% RH
	EMC EMISSION	Compliance to EN55032 (CISPR32) Class B, EN61000-3-2,-3, EAC TP TC 020
	EMC IMMUNITY	Compliance to EN61000-4-2,3,4,5,6,8,11, EN55024, EN61204-3, light industry level, criteria A, EAC TP TC 020
OTHERS	MTBF	504.1K hrs min. MIL-HDBK-217F (25°C)
	DIMENSION	40*90*100mm (W*H*D)
	PACKING	0.3Kg; 42pcs/13.6Kg/0.82CUFT
NOTE	<p>1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature.</p> <p>2. Ripple & noise are measured at 20MHz of</p>	

<p>bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor.</p> <p>3. Tolerance : includes set up tolerance, line regulation and load regulation.</p> <p>4. Length of set up time is measured at cold first start. Turning ON/OFF the power supply may lead to increase of the set up time.</p> <p>5. The power supply is considered a component which will be installed into a final equipment. The final equipment must be re-confirmed that it still meets EMC directives.</p> <p>6. Installation clearances : 40mm on top, 20mm on the bottom, 5mm on the left and right side are recommended when loaded permanently with full power. In case the adjacent device is a heat source, 15mm clearance is recommended.</p> <p>7. The ambient temperature derating of 3.5 /1000m with fanless models and of 5 /1000m with fan models for operating altitude higher°C than 2000m(6500ft).</p>

[DRC-60B Specification](#)