

MD214L



Rating: Not Rated Yet

Price

Sales price without tax 165,00 €

[Ask a question about this product](#)

Manufacturer [Maker: Kinco](#)

Description	Shell Color	Silver White
	Display	4.3" FSTN
	Resolution	192x64 Pixel (Supporting Display Of 4 Lines 12 Chinese Characters)
	Color	Monochromatic
	Brightness	97cd/m ²
	Contrast	Adjustable By Potentiometer
	Backlight	White LED
	LCM Life Time	Greater Than 50,000 Hours At 25±2%, 65±10%RH
	Panel	Non-Touch Screen
	CPU	8-Bit Processor
	Memory	64KB Flash ROM
	Recipe Memory	None
	RTC	None
	Function Key	19 Keys, Customizable (Including 10 Numeric Input Keys)
COM Port	COM0:PC RS232&PLC RS485/422&PLC	

	RS232
CE	EN61000-6-2:2005, EN61000-6-4:2007
Power Supply	21~28VDC
Current	MAX 150mA@24V DC
Interference Immunity Test	Voltage 1500Vp-p, Pulse Cycle 1?s, duration 1?s
Dielectric Strength	500V AC (1min)
Isolation Resistance	Exceed 10M? at 500V DC
Vibration Endurance	10~25Hz (X, Y, Z Direction, 2G, 30 Minutes)
Protection Class	IP65 Front Panel
Operating Temperature	0~50?
Storage Temperature	-20~70?
Operating Humidity	20~90%RH(Non-Condensing)
Shell Material	Engineering Plastic ABS+PC
Dimensions(Wx HxD)	175x90x26 mm
Display Size(WxH)	101x36 mm
Panel Cutout Dimension	165x78 mm
Cooling Method	Natural Air Cooling
Weight	0.3kg

[Kinco HMI MD214L](#)