

MD304L



Rating: Not Rated Yet

Price

Sales price without tax 205,00 €

[Ask a question about this product](#)

Manufacturer [Maker: Kinco](#)

Description	Shell Color	Silver White
	Display	4.3" FSTN
	Resolution	192x64 Pixel (Supporting Display Of 4 Lines 12 Chinese Characters)
	Color	Monochrom atic
	Brightness	97cd/m ²
	Contrast	Adjustable By Potentio meter
	Backlight	White LED
	LCM Life Time	Greater Than 50,000 Hours At 25±2?, 65±10%RH
	Panel	Non-Touch Screen
	CPU	8-Bit Processor
	Memory	64KB Flash ROM
	Recipe Memory	2KB EEPROM
	RTC	Accuracy 30PPM
	Funtion Key	19 Keys, Cu stomizable (Including 10 Numeric Input Keys)

COM Port	COM0:PC RS232&PL CRS485/42 2&PLC RS232
CE	EN61000-6- 2:2005, EN 61000-6-4:2 007
Power Supply	21-28VDC
Current	MAX 150m A@24V DC
Interference Immunity Test	Voltage 1500Vp-p, Pulse Cycle 1?s, Duration 1?s
Dielectric Strength	500V AC (1min)
Isolation Resistance	Exceed 10M? at 500V DC
Vibration Endurance	10~25Hz (X, Y, Z Direction, 2G, 30 minutes)
Protection Class	IP65 Front Panel
Operating Temperature	0~50?
Storage Temperature	-20~70?
Operating Humidity	20~90%RH (Non-Conde nsing)
Shell Material	Engineering Plastic ABS+PC
Dimensions (WxHxD)	175x90x26 mm
Display Size(WxH)	101x36 mm
Panel Cutout Dimension	165x78 mm
Cooling Method	Natural Air Cooling
Weight	0.3 kg

[Kinco HMI MD304L](#)

[Kinco MD304L User Manual](#)