MD304L



Rating: Not Rated Yet
Price
Sales price without tax 205,00 €

Ask a question about this product

ManufacturerMaker: Kinco

Description

Shell Color	Silver White
Display	4.3" FSTN
Resolution	192x64 Pixel (Supporting Display Of 4 Lines 12 Chinese Characters)
Color	Monochromatic
Brightness	97cd/m^2
Contrast	Adjustable By Potentiometer
Backlight	White LED
LCM Life Time	Greater Than 50,000 Hours At 25±2?, 65±10%RH
Panel	Non-Touch Screen
CPU	8-Bit Processor
Memory	64KB Flash ROM
Recipe Memory	2KB EEPROM
RTC	Accuracy 30PPM
Funtion Key	19 Keys, Customizable (Including 10 Numeric Input Keys)

COM Port	COM0:PC RS232&PLC RS485/422&PLC RS232
CE	EN61000-6-2:2005, EN 61000-6-4:2007
Power Supply	21-28VDC
Current	MAX 150mA@24V DC
Interference Immunity Test	Voltage 1500Vp-p, Pulse Cycle 1?s, Duration 1?s
Dielectric Strength	500V AC (1min)
Isolation Resistance	Exceed 10M? at 500V DC
Vibration Endurance	10~25Hz (X, Y, Z Direction, 2G, 30 minutes)
Protection Class	IP65 Front Panel
Operating Temperature	0~50?
Storage Temperature	-20~70?
Operating Humidity	20~90%RH (Non-Condensing)
Shell Material	Engineering Plastic ABS+PC
Dimensions (WxHxD)	175x90x26 mm
Display Size(WxH)	101x36 mm
Panel Cutout Dimension	165x78 mm
Cooling Method	Natural Air Cooling
Weight	0.3 kg

Kinco HMI MD304L

Kinco MD304L User Manual