

2S130Y-039M0



- Phase Current(A): 6~7
- Holding Torque(Nm): 28~40
- Flange Dimension(mm): 132

Rating: Not Rated Yet

Price

Sales price without tax 423,00 €

[Ask a question about this product](#)

Manufacturer[ELCON | Systems & Components](#)

Description	Model	2S130Y-039M0	2S130Y-063R8
	Step Angle	1.8 Degrees ±5%	
	Phase	7	6
	Current (A)		
	Holding Torque (Nm)	40	28
	Damping Torque (Nm)	1.2	0.8
	Winding Resistance (?)	0.9±10%	0.65±10%
	Winding Inductance(mH)	9.5±20%	13.8±20%
	Motor Inertia (Kg.com²)	48.4	33.3
	Motor Length	230	165

Stepper Motors: 2S130Y-039M0

L(mm)		
Number of Lead Wires	4	
Insulation Class	B	
Withstand Voltage Level	500VAC,One Minute	
Max.Axial Load (N)	60	
Max.Radial Load (N)	220	
Operating Temperature	-20??50?	
Surface Temperature Rise	Max.80? ?Rated Phase Current after Two Phases are Connected)	
Insulation Impedance	Minimum 100M?,500VDC	
Weight (Kg)	19	13

[Stepper System](#)