

SMH130D-0157-20AB



?????????: ?? ?????????? ????

Price
Sales price without tax 871,00 €

[?????? ?? ? ?](#)

Manufacturer[ELCON | Systems & Components](#)

Description	Motor Series	Medium Inertia, Flange Size 126mm, 130mm,155mm	
	Model	130D-010 5-20AAK- 2LS	130D-015 7-20AAK- 2LS
	Compatible Driver	ED430-01 05-AA- S-000	ED430-01 57-AA- S-000
	Power Supply VAC	220V	3-phase 220V
	Rated Output Power	1.05KW	1.57KW
	Rated Torque (Nm)	5	7.5
	Maximum Torque (Nm)	15	22.5
	Rated Speed (Rpm)	2000	2000
	Maximum Speed (Rpm)	3000	3000
	Motor Inertia(Kg.com??	7.4	13.1
	Transformer Capacity(KVA)	1.8	2.4
	Encoder	2500p/r (Resolution:10000)	
	Rated Current(A)	4.2	6
	Maximum Current(A)	13.4	18

Torque Constant (Nm/A)		1.19	1.25
Resistance Line-Line (??		1.22	0.98
Inductance Line-Line(mH)		6.08	6.94
Electrical Time Constant (ms)		4.98	7.08
Mechanical Time Constant ?ms)		5.73	7.25
Maximum Radial Force F (N)		1508	1508
Maximum Axial Force F (N)		960	960
Pole pair Number		2	2
Transformer Capacity(KVA)		F	
Encoder		IP65 for Body,Shaft Sealing for IP54	
Environmental Conditions for Operation	Temperature	-20??40? (Non-Freezing)	
	Humidity	Below 90% RH (No Condensing)	
	Ambient Environment	Away from Cctive Gas, Combustible Gas, Oil Drops and Dust	
	Altitude	Maximum Altitude 4000m, Rated Power at 1000m or Below, Above 1000m: Decreasing 1.5% Per 100m Rise	
Motor Weight (Kg)		8	9.5